



Discover  
the potential

Made in Turkey



ISO9001:2008

6000



Dotpeenator™

C09

160X110MM

[www.dotpeenator.com](http://www.dotpeenator.com)

*Perpetuating Your Trade Mark...*

**Dotpeenator™ C09**  
**Dot Peen Marking Machine**  
**Runs with a Computer**  
**Air Driven & Powerful**  
**Z Axis with Double Column**  
**Heavy, Robust & Accurate**  
**Turkish & English Languages**  
**Dot Peen Marking Machine**





## The Contents of the Dotpeenator™ CO9 Standard Package

- Marking Head
- 60cm Double Column
- High Speed Peen/Cartridge Assembly Kit
- Hand Wheel for Height Adjustment
- Work Table w/ T-Slots
- External Start/Stop Remote Control Box
- Air Regulator
- Bracket for Air Regulator
- USB Connection Cable
- CD for Marking Software
- Connection Bolts

## Options for Dotpeenator™ CO9

- Heavy Duty Peen/Cartridge Assembly Kit that Tolerates Uneven Surfaces upto 12mm in Height with a Max of 2000kgf Per Stroke
- Rotary Axis w/ a 80mm Mechanical Chuck
- Rotary Axis w/ a 80mm Air Chuck
- Rotary Axis w/ a 100mm Mechanical Chuck
- Rotary axis w/ a 100mm Air Chuck
- Rotary Table
- Automatic Z Axis
- Name Tag Fixer
- Automatic Tag Feeding System
- Manual or Fixed 2D Data Matrix Code Readers

## Software Specifications of DotPeenator™ CO9

- User Friendly English Software Interface
- Marking Possibility to or From a Database by the Help of SQL Queries
- Log File Followup over 365 Days a Year
- Capability of Marking Date, Julian Date, 2D Data Matrix Codes, Serial Number, Chassis Numbers, Alfanumerical Characters, Symbols, Random Codes and Graphics in Linear & Arc Forms.
- Possibility of Creating Images of Name Tags at the Background of The Screen for Easy Content
- Peen Path Setup for Complex Work Pieces
- Adjustment of Dot Resolution from 0.01mm up
- Over 40 Special Single Line Fonts to Chose from and the Possibility of Marking All TTF Fonts
- Waiting Point Assignment for Peen
- Reverse Marking Capacity

## Mechanical Specifications of Dotpeenator™ CO9

- 160X100mm Marking Area
- Direct Part Marking (DPM) Operations
- 2D Data Matrix Code Marking Operations
- Plastic or Metal Tag Marking Operations
- Marking Almost All Industrial Products from Glass to 63HRC Hardness
- External Start/Stop Remote Control Box
- Integrated Start, Stop and Air Buttons
- USB or RS232 Connection Cables
- Linear Guides
- Manual Z Axis With Hand Wheel or Optional Automatic Z Axis
- Marking Uneven Surfaces upto 12mm Height Without Sacrificing the Marking Quality
- Laser-Like Marking with Its High Speed Peen/Cartridge Assembly Kit
- Cast Iron Work Table w/ T-Slots
- Stainless Steel Axial Dust Covers

## Requirements for Operation

- Any Computer with Windows 98 XP, Vista, 7, 8, 10 Operating Systems
- USB or RS232 Port

